

Schlangenbohrer, Type Lewis



Art. Nr.	GL	Ø	kg	VE
231502	460	6	0,005	1
231508	235	10	0,098	1
231516	235	14	0,005	1
231524	235	18	0,200	1
231526	460	18	0,468	1
231528	235	20	0,005	1
231530	460	20	0,005	1
231532	235	22	0,300	1
231534	450	22	0,642	1
231540	235	26	0,005	1
231544	235	28	0,005	1
231546	460	28	0,005	1

Maschinen-Holzspiralbohrer

aus Werkzeugstahl, zentrisch geschliffen, durchgehende Hinterfräsung mit Zentrierspitze und Vornschneider



Art. Nr.	GL	Ø	kg	VE
230616	70	3	0,005	1
230618	80	4	0,008	1
230620	90	5	0,011	1
230622	100	6	0,015	1
230626	120	8	0,031	1
230628	130	9	0,039	1
230630	137	10	0,047	1
230634	150	12	0,075	1
230636	170	13	0,088	1

Maschinen-Flachzentrumsbohrer

mit zylindrischem Schaft, DIN 6447 A



Art. Nr.	GL	Ø	Schaft/Ø	Schaft kg	VE
230732	150	10	6	0,041	1
230734	150	12	6	0,041	1
230736	150	14	6	0,048	1
230738	150	16	6	0,051	1
230740	150	18	6	0,047	1
230742	150	20	6	0,045	1
230746	150	24	6	0,045	1

Schalungsbohrer

mit zylindrischem Spannschaft, Schneidteil aus Chrom-Vanadium-Stahl



Art. Nr.	GL	Ø	kg	VE
231750	400	6	0,100	1
231752	400	8	0,005	1
231754	400	10	0,160	1
231756	400	12	0,200	1
231758	400	13	0,200	1
231760	400	17	0,005	1
231766	400	22	0,200	1

Hartmetallsteinbohrer DIN 8039

mit zäharten Hartmetallplatten bestückt



Art. Nr.	GL	Ø	SchL	kg	VE
230330	70	3	40	0,003	1
230331	75	3,5	45	0,056	1
230332	80	4	45	0,008	1
230334	85	4,5	50	0,008	1
230336	90	5	50	0,011	1
230338	95	5,5	55	0,012	1
230340	100	6	60	0,018	1
230342	105	6,5	65	0,018	1
230344	110	7	65	0,018	1
230346	120	8	70	0,027	1
230352	140	10	90	0,035	1
230354	150	11	95	0,082	1
230356	160	12	105	0,090	1
230358	170	13	110	0,100	1
230360	180	14	115	0,120	1
230362	190	15	125	0,165	1
230364	190	16	125	0,092	1

Hartmetallsteinbohrer DIN 8039

mit zäharten Hartmetallplatten bestückt



Art. Nr.	GL	Ø	SchL	kg	VE
230370	400	8	300	0,130	1
230372	400	10	300	0,124	1
230374	400	12	300	0,143	1
230376	400	14	300	0,316	1
230378	400	16	300	0,232	1
230380	400	18	300	0,460	1
230382	400	20	300	0,608	1
230400	600	8	500	0,222	1
230402	600	10	500	0,222	1
230404	600	12	500	0,330	1
230406	600	14	500	0,463	1
230408	600	16	500	0,568	1
230410	600	18	500	0,715	1
230412	600	20	500	0,896	1
230414	600	22	500	1,164	1

HM-Betonbohrer "EXTRA"

High-Helix Steinbohrer, sandgestrahlt, gefräste Ausführung, Handwerkerqualität



Art. Nr.	GL	Ø	kg	VE
231700	70	3	0,007	1
231702	85	4	0,011	1
231704	95	5	0,017	1
231706	100	6	0,018	1
231708	100	7	0,020	1
231710	120	8	0,027	1
231712	120	9	0,030	1
231714	120	10	0,035	1
231716	150	11	0,090	1
231718	150	12	0,100	1