



Leiteranschlussklemme, 16-120qmm, f. 5mm



Typ
Art.-Nr.

AKU120/5
107190

Katalog Nr.

Lieferprogramm

Sortiment			60-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	17 x 15
Breite		mm	23.5
Bemessungsbetriebsstrom	I _e	A	440
Cu-Schiene		mm	16 - 120 mm ² AWG 4 - MCM 250.  direkt geklemmt,   4 x 16 x 0.8 oder 6 x 16 x 0.8 oder 10 x 16 x 0.8
verwendbar für			Alle 5 mm dicken Flachschienen
Hinweise ☐ Rundleiter eindrätig  Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse  Rundleiter mehrdrätig  Sektorleiter eindrätig  Sektorleiter mehrdrätig  CU-Band  CU-Schiene			

Approbationen

Product Standards	UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.	E307559
UL Category Control No.	NMTR2, NMTR8
CSA File No.	236217
CSA Class No.	3211-37
North America Certification	UL recognized, CSA certified
Conditions of Acceptability	Refer to approbation report
Specially designed for North America	No
Suitable for	Feeder circuits
Current Limiting Circuit-Breaker	Refer to approbation report
Max. Voltage Rating	600 V AC
Degree of Protection	Feeder circuits

Abmessungen

