



Leiteranschlussklemme, 4-35qmm, 10 mm

Typ
Art.-Nr. **AKU35/10**
107192

Katalog Nr.



Lieferprogramm

Sortiment			60-mm-System 185-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	10.5 x 11
Breite		mm	15.5
Bemessungsbetriebsstrom	I _e	A	270
Cu-Schiene		mm	4 - 35 mm ² AWG 10 - AWG 2.  direkt geklemmt,   3 x 9 x 0.8 oder 6 x 9 x 0.8
verwendbar für			Alle 10 mm dicken Flachschiene
Hinweise  Rundleiter eindrätig  Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse  Rundleiter mehrdrätig  Sektorleiter eindrätig  Sektorleiter mehrdrätig  CU-Band  CU-Schiene			

Approbationen

Product Standards	UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.	E307559
UL Category Control No.	NMTR2, NMTR8
CSA File No.	236217
CSA Class No.	3211-37
North America Certification	UL recognized, CSA certified
Conditions of Acceptability	Refer to approbation report
Specially designed for North America	No
Suitable for	Feeder circuits
Current Limiting Circuit-Breaker	Refer to approbation report
Max. Voltage Rating	600 V AC
Degree of Protection	Feeder circuits

Abmessungen

