



Leiteranschlussklemme, 1,5-16qmm, 10 mm

Typ
Art.-Nr.

AKU16/10
107191

Katalog Nr.



Lieferprogramm

Sortiment			60-mm-System 185-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	7.5 x 7.5
Breite		mm	11.5
Bemessungsbetriebsstrom	I _e	A	180
Cu-Schiene		mm	1.5 - 16 mm ² AWG 14 - AWG 6. direkt geklemmt, 8 x 6 x 0.5
verwendbar für			Alle 10 mm dicken Flachschiene
Hinweise Rundleiter eindrätig Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse Rundleiter mehrdrätig Sektorleiter eindrätig Sektorleiter mehrdrätig CU-Band CU-Schiene			

Approbationen

Product Standards
UL File No.
UL Category Control No.
CSA File No.
CSA Class No.
North America Certification
Conditions of Acceptability
Specially designed for North America
Suitable for
Current Limiting Circuit-Breaker
Max. Voltage Rating
Degree of Protection

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
E307559
NMTR2, NMTR8
236217
3211-37
UL recognized, CSA certified
Refer to approbation report
No
Feeder circuits
Refer to approbation report
600 V AC
Feeder circuits

Abmessungen

