


Anbaugerätestecker
Bestellnr. 1254




- Schraubkontakt
- mit Schutzkappe

Technische Daten

Ampere	32 A
Pole	5 p
Volt	400 V
Uhrzeitstellung	6 h
Hertz	50-60 Hz
Anschluss technik	Schraubkontakt
Kontakt	standard
Schutzart	IP 67
Gewicht	413 g
Prüfzeichen	DE,VDE

Abmessungen



Zeichnung 2 MB 62	Amp. Pole	16			32			63			
		3	5		3	4	5	3	4	5	
Maße in mm											
a		85	85		85	85	85	108	108	108	
b		85	85		85	85	85	101	101	101	
c		132	132		131	131	137	164	164	164	
d		70	70		70	70	70	85	85	85	
e		70	70		70	70	70	77	77	77	
f		6,3	6,3		6,3	6,3	6,3	6,5	6,5	6,5	
g		11	11		11	11	11	12	12	12	
g.1		2	2		2	2	2	2	2	2	
h		100	107		108	108	111	130	130	130	
s		70	87		94	94	102	114	114	114	
l		30	30		30	30	30	40	40	40	
Klemmen für Leiterquer-		1	1		2,5	2,5	2,5	6	6	6	
schnitt von bis mm²		—	2,5	—	—	6	—	—	16	—	