

HALED III GU10 Spotlight

CIVILIGHT



Features


- 99% of halogen lighting effect
- HALED Optical design
- Glare-free
- Switching power supply
- CE and RoHS compliant

Applications

- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes

Part No.	HALEDIII GU10 WC70T7
Halogen Equivalent (W)	70
Wattage (W)	7
Dimmable	NO
Lumens (lm)	500
CRI (Ra)	80
CCT (K)	3000
Beam Angle (deg)	60
Luminous Intensity(cd)	700
Energy Efficiency Class	A
PF	0.5
Voltage (V)	AC200-240
Frequency(Hz)	50/60
Input Current (mA)	53
Socket	GU10
Switching Cycles	100000
Lifespan(hrs)	25000
Working Temperature	-20-40
Storage Temperature (°C)	-20-60
Weight(g)	

Mechanical Drawing



Photometric Diagrams

* Note: Data is subject to change without prior notice. Please visit www.civilight.com for further information.

Cautions

- Power off before replacement
- Don't touch the lamp when lighting
- Don't use it in sealed fixture



CIVILIGHT LIGHTING CO., LTD

Address: 5/F, Building D, HongFa Hi-Tech Park, Shiyan, Shenzhen, China

Tel: +86-755-3368 6619 Fax: +86-755-8602 6609 Web: www.civilight.com