

TQT 3° Slim, Quattro LNB

Art. Number 304877



TRIAX complete range of LNB's

- Great quality, low footprint
- Cutting edge RF technology
- Excellent Cross polar isolation
- Excellent low noise / low phase noise
- High output / low power consumption
- Weatherproof & qualified for harsh environments
- Complete range of Single, Twin, Quad, Quattro, Octo and other types on request

Technical Specifications

ORDER INFORMATION

EAN Number 5061038083972

CHARACTERISTICS

Phase noise @ room temperature - 1 kHz | dBc/Hz -65 dBc/Hz
 Phase noise @ room temperature - 10 kHz | dBc/Hz -85 dBc/Hz
 Phase noise @ room temperature - 100 kHz | -100 dBc/Hz
 Image rejection (min.) | dB 40 dB
 Output VSWR 2.0:1
 Feedhorn diameter | mm Ø 40 mm
 LO temperature drifting ± 2 MHz
 LNB type Quattro

FREQUENCY RANGE

Input frequency low band | GHz 10.7...11.7 GHz
 Input frequency high band | GHz 11.7...12.75 GHz
 Output frequency low band | MHz 950...2150 MHz
 L.O. frequency low band | GHz 9.75 GHz
 L.O. frequency high band | GHz 10.6 GHz
 L.O. technology PLL



Technical Specifications

GAIN

Conversion gain (typ.) dB	63...68 dB
Noise figure max. dB	0,3 dB

ELECTRICAL

Impedance Ω	75 Ω
----------------------	-------------

OPERATIONAL

DC Operating voltage VDC	12...19 VDC
DC Current consumption mA	215 mA
Temperature - operating °C	-30...60 °C

CONNECTORS

Connector Type	F-female
----------------	----------

MECHANICAL

Reflector type	Offset
Colour	RAL 9002 - Grey white
Packing QTY	1
Product Height mm	121.5 mm
Product Width mm	97.6 mm
Product Depth mm	47.1 mm
Packaging Height m	0.128 m
Packaging Width m	0.100 m
Packaging Depth m	0.050 m
Packaging Volume m ³	0.001 m ³
Net Weight kg	0.180 kg
Tara Weight kg	0.026 kg
Total Weight kg	0.206 kg