

## GLM II, Gleitmuttern aus Stahl; galvanisch verzinkt, inkl. Schraube, zur Befestigung in Hohlprofilen



Material		Temp.			
Stahl		-45°C/+250°C			
Art. Bez.	kl [St]	gr [St]	Ko.Gr.	Art.Nr.	
GLM II 4x8	100	2000	24	081 674	
GLM II 4x10	100	2000	24	081 675	
GLM II 4x12	100	2000	24	081 676	
GLM II 4x14	100	2000	24	081 677	
GLM II 4x16	100	2000	24	081 678	
GLM II 4x18	100	2000	24	080 344	
GLM II 4x20	100	2000	24	081 679	
GLM II 4x25	100	2000	24	081 680	
GLM II 4x30	100	2000	24	081 681	

## SBV, Schlitzbandeisen; feuerverzinkt, geschlitzt, in Stangen zu 2 m



Material		Temp.				
Stahl		-45°C/+250°C				
Art. Bez.	Schlitzgröße [mm]	Stegbreite [mm]	kg/m	Bd [m]	Ko.Gr.	Art.Nr.
SBV 20x2	51,0x5,8	10	0,230	20	24	001 699
SBV 20x3	51,0x5,8	10	0,350	20	24	001 700
SBV 30x2	51,0x5,8	10	0,230	20	24	001 701

## SUK, Universalkasten; schwarz aus Guss, mit Deckel und Dichtung



Material		Temp.				
Fe		-45°C/+250°C				
Art. Bez.	Dimension	max. Bohrung [mm]	kl [St]	Ko.Gr.	Art.Nr.	
SUK1	130x130x55	32	1	19	021 892	
SUK2	190x150x75	40	1	19	021 893	

## GM, Typ 8000; aus Messing vernickelt



Material				
Messing vernickelt				
Art. Bez.	kl [St]	Ko.Gr.	Art.Nr.	
GM 17	50	54	054 179	
GM 20	50	54	054 180	
GM 25	25	54	054 277	
GM 32	25	54	054 268	
GM 40	10	54	054 260	
GM 50	10	54	054 079	
GM 63	10	54	054 019	