

**HFXP-HT**, biegsames Panzerrohr mittel, gewellt;  
schwarz (RAL 9005), in Ringen zu 50m bzw. 25m

In Übereinstimmung mit: IEC/EN 61386-22 (ersetzt IEC 60614-2-3, BS 6099), IEC 60423

**HFXP-HT**, pliable conduit medium gauge, cor-  
rugated; black (RAL 9005), in coils of 50m resp. 25m

In accordance with: IEC/EN 61386-22 (replaces IEC 60614-2-3, BS 6099), IEC 60423



Material	Code	Mechan.	UV stabil.	Temp.
PC	EN 3355	> 750 N	<input checked="" type="checkbox"/>	-45°C/+150°C

  

art	dn	di	ps [m]	pl [m]	ref
HFXP-HT 12	13,0	9,0	50	4500	<b>016 574</b>
HFXP-HT 16	16,0	10,7	50	2700	<b>011 301</b>
HFXP-HT 20	20,0	14,1	50	2700	<b>011 302</b>
HFXP-HT 25	25,0	18,3	50	1600	<b>011 303</b>
HFXP-HT 32	32,0	24,3	25	675	<b>011 304</b>
HFXP-HT 40	40,0	30,0	25	500	<b>013 254</b>
HFXP-HT 50	50,0	38,5	25	300	<b>013 255</b>
HFXP-HT 63	63,0	50,0	25	175	<b>019 897</b>