

**KSA, Abstandhalter;** schwarz (RAL 9005), zur Parallelverlegung von Kabelschutzrohren



Material	Temp.
PE	-25 °C / +60 °C

**Basisabstandhalter**

Art. Bez.	dn [mm]	Spezifikation	KoGr	Art.Nr.
KSA 110/3 B	110,0	3-zügig	26	<b>010 423</b>
KSA 110/4 B	110,0	4-zügig	26	<b>010 424</b>

**Doppelabstandhalter**



Art. Bez.	dn [mm]	Spezifikation	KoGr	Art.Nr.
KSA 110/4 D	110,0	4-zügig	26	<b>010 426</b>
KSA 110/6 D	110,0	6-zügig	26	<b>010 427</b>
KSA 110/8 D	110,0	8-zügig	26	<b>010 428</b>
KSA 125/4 D	125,0	4-zügig	26	<b>041 528</b>
KSA 125/6 D	125,0	6-zügig	26	<b>064 285</b>
KSA 125/8 D	125,0	8-zügig	26	<b>041 939</b>
KSA 160/4 D	160,0	4-zügig	26	<b>024 325</b>
KSA 160/6 D	160,0	6-zügig	26	<b>064 284</b>
KSA 160/8 D	160,0	8-zügig	26	<b>021 725</b>

**KVK, Verschlusskappe;** gelb, rot oder transparent, verhindert das Eindringen von Fremdkörpern



Material
PE

Art. Bez.	dn [mm]	KoGr	Art.Nr.
KVK 50	50,0	26	<b>038 173</b>
KVK 63	63,0	26	<b>038 174</b>
KVK 65	65,0	26	<b>020 902</b>
KVK 75	75,0	26	<b>020 903</b>
KVK 80	80,0	26	<b>020 904</b>
KVK 90	90,0	26	<b>020 905</b>
KVK 100	100,0	26	<b>020 906</b>
KVK 110	110,0	26	<b>020 907</b>
KVK 125	125,0	26	<b>020 908</b>
KVK 160	160,0	26	<b>020 910</b>
KVK 200	200,0	26	<b>020 911</b>