













Leiteranschlussklemme, 1,5-16qmm, f. 5mm

Typ **AKU16/5**
Art.-Nr. **107187**

Katalog Nr.

Lieferprogramm

Sortiment			60-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	7.5 x 7.5
Breite		mm	11.5
Bemessungsbetriebsstrom	I_e	A	180
Cu-Schiene		mm	1.5 - 16 mm ² AWG 14 - AWG 6.  direkt geklemmt,   8 x 6 x 0.5
verwendbar für			Alle 5 mm dicken Flachschienen
Hinweise			
 Rundleiter eindrätig			
 Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse			
 Rundleiter mehrdrätig			
 Sektorleiter eindrätig			
 Sektorleiter mehrdrätig			
 CU-Band			
 CU-Schiene			

Approbationen

Product Standards
UL File No.
UL Category Control No.
CSA File No.
CSA Class No.
North America Certification
Conditions of Acceptability
Specially designed for North America
Suitable for
Current Limiting Circuit-Breaker
Max. Voltage Rating
Degree of Protection

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
E307559
NMTR2, NMTR8
236217
3211-37
UL recognized, CSA certified
Refer to approbation report
No
Feeder circuits
Refer to approbation report
600 V AC
Feeder circuits

Abmessungen

