

Illuminable double push button, 2x NO or NC

With small transparent windows without symbol. The LED lighting elements need to be ordered separately (see accessories).

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).






Illuminable double push button, 2x NO or NC

With small transparent windows without symbol. The LED lighting elements need to be ordered separately (see accessories).
The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).






COMPLETE UNIT WITH PLUG-IN TERMINALS, EXCLUDING BOX (IP55)



	700-35105	Pieces: 10	With plug-in terminals, grey
	701-35105	Pieces: 10	With plug-in terminals, white
	761-35105	Pieces: 10	With plug-in terminals, black

COMPLETE UNIT WITH SCREW TERMINALS, EXCLUDING BOX (IP55)



	700-35100	Pieces: 10	With screw terminals, grey
	701-35100	Pieces: 10	With screw terminals, white
	761-35100	Pieces: 10	With screw terminals, black

700-35105

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, grey



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: light grey with dark grey button.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, grey. The sockets are equipped with plug-in terminals with a release for clamping the wires. The releases can be controlled from the front side by hand or with a screwdriver. All connection terminals are located at the top of the end socket and can contain up to 2 x 2.5 mm² of wire. The stripping length (12 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: -25 – +55 °C
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The switch is light grey RAL 7035 (NCS S1502-B) and the control button is dark grey (NCS S3502-B).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



701-35105

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, white



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: white.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, white. The sockets are equipped with plug-in terminals with a release for clamping the wires. The releases can be controlled from the front side by hand or with a screwdriver. All connection terminals can contain up to $2 \times 2.5 \text{ mm}^2$ of wire. The stripping length (12 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens ($6.7 \times 6.7 \text{ mm}$) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: $-25 - +55 \text{ }^\circ\text{C}$
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of $-25 \text{ }^\circ\text{C}$ and a maximum temperature of $55 \text{ }^\circ\text{C}$
- Colour: The base material is coloured in mass, white (RAL 9010).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



761-35105

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, black



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: black.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box, with plug-in terminals, black. The sockets are equipped with plug-in terminals with a release for clamping the wires. The releases can be controlled from the front side by hand or with a screwdriver. All connection terminals are located at the top of the end socket and can contain up to 2 x 2.5 mm² of wire. The stripping length (12 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: -25 – +55 °C
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



700-35100

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: light grey with dark grey button.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box. The push button is equipped with block-shaped, silver contacts (cadmium-free) in the form of a cross. The mechanism is equipped with connection terminals with combination screwheads (Pz1 slot 0.85 x 5 mm). Each screw is also equipped with a screwdriver slot that prevents the screwdriver from sliding off the screwhead. All connection terminals can contain up to 2 x 2.5 mm² of wire. The stripping length (8 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: -25 – +55 °C
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The switch is light grey RAL 7035 (NCS S1502-B) and the control button is dark grey (NCS S3502-B).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



701-35100

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: white.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box. The push button is equipped with block-shaped, silver contacts (cadmium-free) in the form of a cross. The mechanism is equipped with connection terminals with combination screwheads (Pz1 slot 0.85 x 5 mm). Each screw is also equipped with a screwdriver slot that prevents the screwdriver from sliding off the screwhead. All connection terminals can contain up to 2 x 2.5 mm² of wire. The stripping length (8 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: -25 – +55 °C
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, white (RAL 9010).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



761-35100

4 year warranty

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box



This illuminable, surface-mounting, double push button is equipped with two buttons and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof, surface-mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. The lighting units must be ordered separately. Colour combination: black.

The Niko Hydro products are not suitable for use in ammonia rich environments (e.g. pig houses).

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, excluding surface-mounting box. The push button is equipped with block-shaped, silver contacts (cadmium-free) in the form of a cross. The mechanism is equipped with connection terminals with combination screwheads (Pz1 slot 0.85 x 5 mm). Each screw is also equipped with a screwdriver slot that prevents the screwdriver from sliding off the screwhead. All connection terminals can contain up to 2 x 2.5 mm² of wire. The stripping length (8 mm) of the wires and the wiring diagram are indelibly indicated at the back of the base. The terminals and the switch symbol are indelibly indicated at the front. The bottom of the base is provided with two rectangular recesses for the integration of two lighting units. A lighting unit with wires can be clicked in the left and right recess. At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units. The function is designed to be mounted in a splashproof, surface-mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box.

Cable space: Two laterally positioned holders inside the outlet hold the mechanism in place. A snap connector holds the wired mechanism in place. There is 21.9 mm of wiring space remaining under the mechanism. The cover has an integral closure and is hermetically sealed onto the appropriate box. The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94 V2/1.6 mm). The control button is made of rigid ABS.

- Number of mechanisms: 1
- Ambient temperature: -25 – +55 °C
- Protection degree: The combination of a Hydro mechanism + flush or surface mounting box has a protection degree of IP55
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE

