

**Art.-Nr. 9068-PRI**

- Optimal geeignet für (Hochvolt-) Halogeneinbaustrahler, LED
- Schützt LED vor Überhitzung
- Einfacher und nachträglicher Einbau
- Aktiver Brandschutz in Hohlwanddecken

**Technische Daten****Sonstige Eigenschaften**

Farbe	transparent
Material	Silikon-Kautschuk
EAN	4260182060841
Zolltarif-Nr.	40169997

Geeignete Leuchten: Niedervoltleuchten mit max. 35 W mit AL-Reflektor (keine Kaltlichtlampen).

**Abmessungen & Verpackungen**

Einbautiefe	100 mm
Aussendurchmesser	68 mm
Auslassöffnung	66 mm
Klappenlänge	50 mm
Klappenbreite	26 mm
Rand Lampenöffnung	5 mm
Stärke Kappe	0,8 – 1,0 mm
Verpackungseinheit	10 Stück
Verpackungseinheit UM-Karton	250 Stück



**Order-no. 9068-PRI**

- Optimally suited for (high voltage) halogen recessed spotlights, LED
- Protects LED against overheating
- Easy and subsequent installation
- Active fire protection in hollow wall ceilings

Data sheet



**Technical data**

**Other characteristics**

Colour	transparent
Material	silicone rubber
EAN	4260182060841
Customs tariff number	40169997

Suitable luminaires: low-voltage luminaires with max. 35 W with AL reflector (no cold light lamps).

**Dimensions & packaging**

Installation depth	100 mm
Outer diameter	68 mm
Outlet opening	66 mm
Flap length	50 mm
Flap width	26 mm
Edge lamp opening	5 mm
Thickness cap	0.8 - 1.0 mm
Packing unit	10 pieces
Packaging unit UM catron	250 pieces