



Art.-Nr. P008-D / P009-D

- Optimal geeignet für Halogeneinbaustrahler, LED
- Schützt LED vor Überhitzung
- Einfacher und nachträglicher Einbau
- Aktiver Brandschutz in Hohlwanddecken



Lampenleistung max. 35 W (nicht geeignet für Kaltlichtlampen).

Technische Daten

Sonstige Eigenschaften

Farbe	transparent
Material	Silikon-Kautschuk
EAN (P008-D)	4260182060148
EAN (P009-D)	4260182060155
Zolltarif-Nr.	40169997


Abmessungen & Verpackungen

Einbautiefe	70 mm
Aussendurchmesser	68 mm / 75 mm
Auslassöffnung	66 mm / 73 mm
Leuchteneinbauhöhe	67 mm
Klappenlänge	50 mm
Klappenbreite	26 mm
Rand Lampenöffnung	5 mm
Stärke Kappe	0,8 – 1,0 mm



Order-no. P008-D / P009-D

- Optimal for halogen spotlights, LED
- Easy subsequent installation
- Protects LED against overheating
- Active fire prevention



Lamp power max. 35W (not suitable for cold light bulbs).

Technical data

Other characteristics

Colour	transparent
Material	silicone rubber
EAN (P008-D)	4260182060148
EAN (P009-D)	4260182060155
Customs tariff number	40169997

Dimensions & packaging

Installation depth	70 mm
Outer diameter	68 mm / 75 mm
Outlet opening	66 mm / 73 mm
Luminaire installation height	67 mm
Flap length	50 mm
Flap width	26 mm
Edge lamp opening	5 mm
Thickness cap	0.8 -1.0 mm