



## QuickFix® Extension 3

Predecessor: 014-014

**001-106**

QUICK-FIX3MWH

### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our patented Quick-Fix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### Dimensions

 white

Length: 3.00 m  
 Number of segments: 1  
 Length per segment: 3.00 m  
 Max. Wattage: 1800 W

Operating voltage: 220-240 V AC 50-60Hz  
 Operating mode:  
 Outlets: 1  
 Connectable: no

### Packaging - Product

Type of Packaging: Blister with headcard  
 EAN-Code: 9120079030102  
 Size (L-W-H): 17 x 25 x 0 cm  
 Weight: 0.29 kg  
 Produkts/Packaging: 1

### Packaging - Shipping

Type of Packaging: Brown carton  
 EAN-Code: 9120079034896  
 Size (L-W-H): 42 x 30 x 26 cm  
 Weight: 10.44 kg  
 Produkts/VPE: 30



QuickFix® connection system